

ENLARGED FOR CLARITY

CHOICE OF POSITIVE LOCKING IN BOTH DIRECTIONS IN EXTENDED POSITION OR STOP-OUT ONLY WHICH ENABLES EASY ENTRY OF CHASSIS INTO CABINET WITHOUT MANIPULATION OF CATCHES.

NOTES:


- SOLID BEARING, SUPERIOR PERFORMANCE AGAINST HIGH SHOCK AND VIBRATION.
- BUILT IN PERMANENT DRY LUBRICANT, NEVER NEEDS OILING.
- ALL HARDWARE STAINLESS STEEL OR ZINC PLATED.
- FINISH: MOLYBDENUM DISULPHIDE.
- DRY LUBRICANT, BAKED ON AT 400° PER MIL - L - 25504 OVER PHOSPHATE COATING PER MIL - P - 16232, TYPE M.
- MATERIAL: PRIME HARD COLD ROLLED STEEL. ALL PARTS BUILT TO MILITARY SPECIFICATIONS.
- SLIDES SHIPPED WITH STANDARD 2" REAR MOUNTING BRACKETS. IF SPECIFIED, ANY ONE OF THE FOLLOWING SIZE REAR MOUNTING BRACKETS WILL BE SHIPPED WITH SLIDES. 4", 6", 8", 10" OR 12".
- LOAD RATINGS: NOMINAL LOAD RATING 75* POUNDS.

*Load ratings are based on a pair of 18" slides with standard extension.

TO ORDER, PLEASE SPECIFY FEATURE NEEDED:
 EST - 20 - PL (POSITIVE LOCKING WHEN EXTENDED)
 EST - 20 - SO (STOP - OUT ONLY)
 -FD (FAST DISCONNECT)

SLIDE DIMENSIONS						
MODEL NO.	L	T	A	B	C	D
EST - 10	10	11	3.12	6.25		
EST - 12	12	13	3.75	7.50		
EST - 14	14	15	4.37	8.75		
EST - 16	16	17	5.00	10.00		
EST - 18	18	19	5.62	11.25		
EST - 20	20	21	3.125	6.250	9.375	12.500
EST - 22	22	23	3.937	7.875	11.812	15.750
EST - 24	24	25	4.437	8.875	13.312	17.750
EST - 26	26	27	4.937	9.875	14.812	19.750
EST - 28	28	29	5.437	10.875	16.312	21.750
EST - 30	30	31	5.937	11.875	17.812	23.750

OCTOBER 1977



BARNES ENGINEERING COMPANY
 2715 DELTA PLACE
 COLORADO SPRINGS, CO 80910
 800-995-6050 PHONE
 719-390-6700 FAX
 www.slimtrack.com

SLIM TRACK 3-SECTION SOLID BEARING SLIDES